



Unit 7 Swan Business Centre, Buckingham, MK18 1TB
01280 817304
01280 817185
sales@bellflowsystems.co.uk



BDP-200

200 l/min · 2.2 kW

High flow pump



code 10100

G140a



mm (approx.) 285 880 325 kg (approx.) 85.5

USE

• **Bedplate Vane pump of high flow, self-suction, positive displacement, constant flow, inaudible, and heavy-duty.**

- The transfer is quick, uniform, and inaudible.
- The pump has a built-in bypass valve.

- It is specially intended for the transfer of high volumes, S-1 service, continuous for fuel tank charging and discharging, storage of fuel, and any non-corrosive and chemical liquid without solid particles in suspension.

TECHNICAL DATA

PUMP

- Flow: **200 l/min**
- Operation pressure: 3.5 bar
- 740 rpm
- Connection through weldable flange of 1 1/2"
- **Recommended diameters:**
suction and delivery connection: Ø2"
- Motopump group performance: horizontal
- Bypass built-in
- Material:
Body: GG-20 EN GJL-200 cast iron
Shaft: F114
Blades: Duravane (PPS with 15 % PTFE + 30 % fiberglass)
- Mechanical pump seal: DIN 24960
- Pump/reducer coupling: elastic (Martin Flex 40H-1108/19-22)

MOTOR

- Voltage: 230-400 VAC triphase
- Frequency: 50 Hz
- Power: 2.2 kW
- Material: aluminium
- IP-55 protection
- Condensable protection: encapsulated
- ATEX EExd IIBT4 Certificate
- Turn speed: 3,000 rpm
- Aislamiento: Clase F
- Constructive shape: horizontal B5
- Reducer/motor coupling: flange
- Noise level: 80 dB(A)

REDUCER

- Type: helical gear
- Inlet: 3,000 rpm · Outlet: 740 rpm
- Ratio: 3.9
- Model: IPC-102/3,9/200-24

